



INTERPRETATION LEGEND

INDUCED POLARIZATION SURVEY	
RESISTIVITY	CHARGEABILITY
Highly conductive	Very High (80 > 20 mV/V)
Conductive	High (15.0 - 80 < 20 mV/V)
Resistive	Moderate (5.0 - 15.0 mV/V)
Very resistive	Weak (2.0 - 5.0 mV/V)
	Very weak (0.2 - 2.0 mV/V)
Interpreted IP Axis:	

Relative Contrast of Chargeability (Ground Model at 25 m of Vertical Depth)

> 22.0 mV/V	
15.0 to 22.0 mV/V	
10.0 to 15.0 mV/V	
7.5 to 10.0 mV/V	
5.5 to 7.5 mV/V	
4.5 to 5.5 mV/V	
3.5 to 4.5 mV/V	
< 3.5 mV/V	

- Other Symbols**
- Mineral occurrence:
 - Old DDH:
 - Inferred Fault:
 - Proposed DDH:



Map Projection
 Datum: NAD83-CSRS
 Ellipsoid: GRS80
 Projection: UTM
 Central Meridian: 93°W (Zone 15)
 Central Scale Factor: 0.9996
 False Easting/Northing: 500,000m/0m
 Major Axis: 6378137

Thierry IP Chargeability Survey (Figure 1)